

LWW-SL-RGBW

HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

Project _____
Location _____
Quote/ Ref # _____

The **LWWSL-RGBW** Mini LED Wall Washer is a high-performance low voltage luminaire designed for outdoor facade lighting. It is available in 500mm and 1000mm. It features color-changing ability with high radiance for an optimal color scheme. The multiple optic designs and anti-glare louver making this luminaire extremely versatile in supporting to a variety of architecture applications.



SPECIFICATIONS

INPUT VOLTAGE	24V DC
POWER CONSUMPTION	18W per Ft. (20") 36W per Ft. (40")
CRI	90+
COLOR TEMPERATURE	RGB30K / RGB40K / RGB65K
DIMMING	TRIAC
MAX RUN	Linkable up to 6 fixtures (assorted)
OPERATING TEMPERATURE	14°F (-10°C) - 122°F (50°C)
STORAGE TEMPERATURE	-22°F (-30°C) - 140°F (60°C)
BEAM ANGLE	15° / 25° / 35° / 50° / 20°x50°
IP RATING	IP66 wet location (outdoor)
LUMEN MAINTENANCE	50,000 hrs.

FEATURES

- 360 lumens per foot
- Linkable up to 6 fixtures (assorted lengths)
- Proprietary Optical Technology
- DMX Ready
- Proprietary Adjustable Mounting Bracket
- Facade Wall Washing
- Graze Lighting
- Signage




MODEL	LENGTH	COLOR TEMP	OPTICS	OPTIONS	FINISH	VOLTAGE
LWWSL	20 20" (18W)	RGB30K RGB3000K	15 15°	STB Standard Tilting Bracket	TG Titanium Grey	24 24V DC
	40 40" (36W)	RGB40K RGB4000K	25 25°	ETB Extended Tilting Bracket	*BK Black	
		RGB65K RGB6500K	35 35°	LTB L-Shape Bracket	*WH White	
			50 50°	WMA Extended Mounting Arms		
			20x50 20° x 50°	STK Ground Stake		

* Special order item- allow up to 4 weeks of lead time


LWW-SL-RGBW

HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

DIMENSIONS



OPTICS




LWW-SL-RGBW


HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

MOUNTING ACCESSORIES


LWW-SL-STB
STANDARD TILTING BRACKET
*Included with every Fixture




LWW-SL-ETB
EXTENDED TILTING BRACKET
*Sold Separately




LWW-LTB
L-SHAPED BRACKET
*Sold Separately



LWW-WMA
EXTENDED MOUNTING ARMS
*Sold Separately



LWW120-STK
MOUNTING STAKE
*Sold Separately




LWW-SL-RGBW



HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

COMPATIBLE ACCESSORIES



LWW-EC
END CAP
*Sold Separately



LWW-SL-12-ADLV
LWW-SL-24-ADLV
LWW-SL-36-ADLV
LWW-SL-48-ADLV
12", 24", 36", 48" ASYMMETRIC LOUVER
*Sold Separately



LWW-SL-12-SDLV
LWW-SL-24-SDLV
LWW-SL-36-SDLV
LWW-SL-48-SDLV
12", 24", 36", 48" SYMMETRIC LOUVER
*Sold Separately



LWW-LNK-10
LWW-LNK-36
LWW-LNK-72
10", 36", 72" LINK EXTENSION CABLE
*Sold Separately



LWW-HWC-72-BK
72" HARDWIRE CABLE
*Sold Separately



LWW-SL-RGBW


HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

DMX CONTROLLERS

RGB CT600

MULTI-FUNCTION RGBW WALL CONTROLLER


INPUT VOLTAGE	5V DC, 1A
OUTPUT SIGNAL	RF 2.4GHZ + DMX512
CONTROL	4 ZONES
COLOR OPTIONS	Black/ White
WORKING TEMP	-20°C ~ 40°C
DIMENSIONS	LxWxH (5.19"x7.08"x1.38")



RGB-SDE3

WiFi DMX WALL CONTROLLER

INPUT VOLTAGE	6V DC, 0.6A
OUTPUT SIGNAL	DMX512 (x2)
PROGRAMMABILITY	PC/ MAC/ Tablet/ Smartphone
COLOR OPTIONS	Black/ White
CONNECTIONS	USB/ Ethernet/ RS232/ CLock/ 8dry contact ports/ 5V output relay
MEMORY	MicroSD Card
WORKING TEMP	-20°C ~ 40°C
DIMENSIONS	LxWxH (5.75"x4.17"x0.43")



LWW-SL-RGBW

HIGH-OUTPUT MINI RGB/RGBW LED WALL WASHER

COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES

NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"

