CSL-225

DIRECT / INDIRECT SUSPENDED LED LUMINAIRE

The **CSL-225** is designed with a simple structure combined with the direct-indirect lighting concept which can provide uniform light output and excellent anti-glare effect. Advanced thermal management technology guarantees continuous high lumen output and constant CCT.

SPECIFICATIONS

TYPE
INPUT VOLTAGE
POWER CONSUMPTION
LUMEN OUTPUT
AVAILABLE LENGTHS
FINISH
COLOR TEMPERATURE
CRI
DIMMING
LENS
POWER FEED
LIGHTING DISTRIBUTION
DRIVER
IP RATING
CERTIFICATIONS

Suspended 120V-277V 6W - 8W Up to 1,000 Lm/ Ft. 4 Ft. / 6 Ft. / 8 Ft. White / Black / Silver 27K / 30K / 35K / 40K / 50K 90+ ELV, 0-10V and TRIAC Frosted Acrylic Lens 10Ft. Up & Down Remote or Internal Dry and Damp Location UL Listed

FEATURES

- Up to 1,000 Lm/ Ft.
- 118 Lm/ W
- 90+ CRI
- Aircraft cable suspension system
- High quality aluminum alloy
- Internal driver available for DIRECT option
- UL Listed (US and Canada)

LUMENS

TYPE	WATTS (W/ FT.)	LM/FT	
LI	6W	500	
L2	7W	800	
L3	8W	1000	



MODEL	LENGTH	DOWN	UP	COLOR TEMP	FINISH	VOLT	MOUNTING	OPTIONS
CSL225	4 4 Ft. 6 Ft. 8 Ft. 8 Ft.	DL1 500 Lm DL2 800 Lm DL3 1000 Lm	UL1 500 Lm UL2 800 Lm UL3 1000 Lm	27K 700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White Black Silver	UNV 120-277V	C12 12ft cable Custom (XX=ft, ceiling to top of fixture)	INTERNAL: EBINT* Electronic/ TRIAC DIOINT 1% 0-10V REMOTE: EB Electronic/ TRIAC DIO 1% 0-10V

CORE A R C H I T E C T U R A L L I G H T I N G UPDATED: 0130.25




CSL-225



DIRECT / INDIRECT SUSPENDED LED LUMINAIRE

DIMENSIONS



SUSPENSION KIT ACCESSORIES

POWER FEED KIT

ALP-CF-WH WHITE POWER FEED KIT

ALP-CF-BK BLACK POWER FEED KIT

* SOLD SEPARATELY



2" NON-POWER FEED KIT

ALP-CSB-WH-2 2" WHITE FEED KIT

ALP-CSB-BK-2 2" BLACK FEED KIT

*SOLD SEPARATELY





DIRECT / INDIRECT SUSPENDED LED LUMINAIRE

SUSPENSION KIT ACCESSORIES

5" NON-POWER FEED KIT

ALP-CSB-WH-5 5" WHITE FEED KIT

ALP-CSB-BK-5 5" BLACK FEED KIT

*SOLD SEPARATELY

